Additional File 7

Classifying short genomic fragments from novel lineages using composition and homology

Donovan H. Parks^{1,§}, Norman J. MacDonald^{1,§}, and Robert G. Beiko^{1,*}

¹Faculty of Computer Science, Dalhousie University, 6050 University Avenue, Halifax, Nova Scotia, Canada B3H 1W5

^{*} To whom correspondence should be addressed (beiko@cs.dal.ca).




Figure S13. Percentage of classified query fragments of length 400 bp assigned to the correct rank, correct lineage, or incorrectly. Each set of bars indicates the performance at a given rank when the child lineages of that rank are excluded from the training set. For example, results at the genus level are calculated with species-level lineages excluded. Performance is reported at species (S), genus (G), family (F), order (O), class (C), phylum (P), and domain (D) ranks. The rank-specific NB-BL classifier always classifies query fragments at the strain level and as a result never assigns fragments to the correct rank. BLASTN and LCA results are for an E-value threshold of 10^{-5} . The LCA classifiers use p=15% and the ε-NB classifier uses $ε=10^{5}$.




Figure S14. Percentage of classified query fragments of length 1000 bp assigned to the correct rank, correct lineage, or incorrectly. Each set of bars indicates the performance at a given rank when the child lineages of that rank are excluded from the training set. For example, results at the genus level are calculated with species-level lineages excluded. Performance is reported at species (S), genus (G), family (F), order (O), class (C), phylum (P), and domain (D) ranks. The rank-specific NB-BL classifier always classifies query fragments at the strain level and as a result never assigns fragments to the correct rank. BLASTN and LCA results are for an E-value threshold of 10^{-5} . The LCA classifiers use p=15% and the ε-NB classifier uses $ε=10^{5}$.

[§] These authors contributed equally to this work.